

**PRODUCT NAME: Rhino Hybrid™ HP 11-50 Resin Black**
**SECTION 1 – IDENTIFICATION**

**Manufacturer's Info:**  
**Rhino Linings Corporation**  
 9747 Businesspark Avenue  
 San Diego, CA 92131

**Information phone:** (858) 450 0441  
**Emergency contact:** CHEMTREC (800) 424 9300

**Product name:** Rhino Hybrid™ HP 11-50 Resin Black  
**Chemical Name:** Polyol/Polyamine Blend  
**Chemical Family:** Polyurethane/Polyurea Hybrid Resin  
**Product Category:** Component of Polyurethane/Polyurea Hybrid System  
**Recommended use:** Spray Elastomer

**SECTION 2 – HAZARD(S) IDENTIFICATION**
**OSHA Hazard Communication Standard:**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**GHS-Label Elements:**      **Signal Word:**  
 WARNING

**Pictogram(s):**



GHS 08



GHS 07

**Classification of the substance or mixture:**

Hazard Class	Category	Hazard Statement Codes	Hazard Statements
Acute Toxicity, Oral	4	H302	Harmful if swallowed
Acute Toxicity, Dermal	5	H313	May be harmful in contact with skin
Serious eye damage / Eye irritation	2A	H319	Causes serious eye irritation
Carcinogenicity	2	H351	Suspected of causing cancer by inhalation
Specific target organ toxicity, repeated exposure	2	H373	May cause damage to kidney, liver and pancreas through prolonged or repeated exposure May cause damage to respiratory system/lungs through prolonged or repeated exposure by inhalation
Aquatic Hazard, Acute	2	H402	Harmful to aquatic life
Aquatic Hazard, Chronic	2	H412	Harmful to aquatic life with long lasting effects

**Precautionary Statements:**

Prevention:	P201	Obtain special instruction before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P281	Use personal protective equipment as required.
	P260	Do not breathe mist, vapors, spray.
	P270	Do not eat, drink, and smoke when using this product.
	P264	Wash exposed area with plenty of water and soap thoroughly after handling.
	P272	Contaminated work clothing should not be allowed out of the workplace.
	P273	Avoid release to the environment.
Response:	P301 + P312 + P330	<b>IF SWALLOWED:</b> Call a POISON CENTER or doctor/physician. Rinse mouth.
	P302 + P352	<b>IF ON SKIN:</b> Wash with plenty of soap and water.
	P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
	P363	Wash contaminated clothing before reuse.
	P305 + P351 + P338	<b>IF IN EYES:</b> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337 + P313	If eye irritation persists: Get medical advice/attention.
	P308 + P313	<b>IF exposed or concerned:</b> Get medical advice/attention.
	P314	Get medical advice/attention if you feel unwell.
	P391	Collect spillage.

**Date: November 27, 2019**

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/container to hazardous or special waste collection point in accordance with local/regional/national/international regulations.

**Hazards not otherwise classified:** Not known.

**Note:** Negative effects of the component classified as carcinogen are minimized since it is dispersed in a liquid as opposed to an inhalable fine powder form. However, precautions should be taken to avoid breathing mists created by heating, mixing or spraying and dust from cutting or grinding of cured product containing this component.

**SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

Components	CAS #	EC #	Concentration, %
Rhino Poly 170™	Proprietary	Proprietary	65 – 75
Diethyltoluenediamine	68479-98-1	270-877-4	5 – 10
Polycaprolactone triol	37625-56-2	500-099-5	5 – 10
2,2',2''-nitrilotriethanol	102-71-6	203-049-8	5 – 10
Zeolites	1318-02	930-915-9	1 – 5
Black Pigment (contains Carbon Black)	1333-86-4	215-609-9	1 – 5

**SECTION 4 – FIRST-AID MEASURES****Description of First Aid measures:**

**Inhalation:** Move to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory problems, seek medical attention.

**Skin:** Wash material off of the skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes immediately and wash them before reuse. Get medical advice/attention if irritation or rash occurs.

**Eye:** Rinse cautiously with water for several minutes, especially under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Do not rub eyes in order to prevent corneal injury. Get medical advice/attention if eye irritation persists.

**Ingestion:** Immediate medical attention required. Call a poison center or physician. Remove exposed person to fresh air and keep at rest in a position comfortable for breathing. Remove dentures if any. If the exposed person is conscious, rinse mouth with water and then give plenty of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Do not induce vomiting unless directed to do so by medical personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

**Most important symptoms/effects, acute and delayed:** See Section 11 for more details.

**General advice for First Aid responders:** No action should be taken involving any personal risk or without suitable training. If potential for exposure exist refer to Section 8 for specific personal protective equipment. Show this SDS to physician.

**Note to physician:** Treatment should be supportive and based on the judgment of the physician in response to the reaction of the patient. Recommended medical monitoring for at least 24 hours. Certain ingredient of this product may cause methemoglobin formation resulting in a reduced ability of the blood to carry oxygen; a symptom may include cyanosis. Immediately give oxygen if victim turns blue (lips, ears, fingernails). Since reversion of methemoglobin to hemoglobin occurs spontaneously after termination of exposure, moderate degrees of cyanosis need to be treated only by supportive measures.

**SECTION 5 – FIRE-FIGHTING MEASURES**

**Suitable extinguishing media:** Water fog or fine spray, alcohol-resistant foam, dry chemical or carbon dioxide fire extinguishers.

**Unsuitable extinguishing media:** Direct water stream may cause frothing, splattering of burning material and spreading of fire.

**Specific hazards arising from the chemical:** Material may be ignited only if preheated to high temperatures (such in fire conditions). Fire in vicinity poses risk of pressure build-up and rupture. Containers at risk from fire should be cooled with water and, if possible, removed from the danger area. Hazardous combustion products: carbon and nitrogen oxides, amines, hydrogen cyanide, lower molecular weight organic molecules.

**Special Protective Equipment and Precautions for fire-fighters:** Wear NIOSH or OSHA approved self-contained breathing apparatus in positive pressure mode with full face piece and full protective gear. Isolate the scene by removing all persons from the incident area. No action should be taken involving any personal risk or without suitable training. Spilled product will cause very slippery walking surfaces.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures:** Keep unnecessary and unprotected personnel from entering. Ensure adequate ventilation/exhaust extraction. Avoid breathing vapors or mist during clean up. Use protective equipment as described in Section 8. Do not touch or walk through spilled material; spilled material may cause a slipping hazard.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Inform the relevant authorities if the product has caused environmental pollution. Water polluting material. May be harmful to the environment if released in large quantities. See Section 12.

**Methods and materials for containment and cleaning up:** Remove mechanically; cover the remainder with non-combustible absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth). Following absorption, transfer into properly labeled chemical waste containers. If necessary, repeat application of absorbent material until all liquid has been removed from the surface. Wash the spill site with soap and water. Cover container and remove from work to a well ventilated area. Properly dispose of the waste material and any contaminated equipment (i.e., broom or brush) in accordance with existing federal, state and local regulations.

For major spills: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Wash spillages into an effluent treatment plant or contain and collect with an absorbent material as described in the previous paragraph.

For minor spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly with soap and water to remove residual contamination. Never return spills to original containers for re-use.

Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, see Section 1 for the Emergency contact; for further disposal measures, see Section 13.

**SECTION 7 – HANDLING AND STORAGE**

**Precautions for safe handling:** Protect chemical from atmospheric moisture. Avoid prolonged exposure to heat and air. Keep away from sources of ignition. Do not reseal if contamination is suspected.

Use adequate ventilation to keep airborne levels below the exposure limits. Do not breathe vapors and mists. Wear respiratory protection if material is heated, mixed, sprayed or used in a confined space. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash hands thoroughly after handling. Hands and/or face should be washed before eating, drinking and smoking and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas.

**Conditions for safe storage, including any incompatibilities:** Store in original or approved alternative container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect it against physical damage and moisture. Normal temperature and pressures do not affect the material. Keep liquid away from heat, sparks and flame. Do not cut, drill, grind, weld or perform similar operations on or near containers. Use appropriate containment to avoid environmental contamination. Segregate from acids and acid forming substances.

**Storage stability:** Stable under normal conditions.

**Storage temperature:** 60 - 90°F (16 – 32°C)

Date: November 27, 2019

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200. Employees and consumers should be warned of health risks associated with product use. See Section 8 for additional information on hygiene measures.

**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION****Occupational exposure limits (OEL):****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m <sup>3</sup>	---

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m <sup>3</sup>	---

**Appropriate engineering controls:** Good local and general ventilation should be sufficient to control worker exposure to airborne contaminants below recommended exposure limits. Local exhaust may be required in some areas.

**Personal protective equipment:****Eye/face protection:**

When directly handling liquid product, eye protection is required. Examples of eye protection include safety glasses and goggles or full face shield when there is a greater risk of splash. Contact lenses should not be worn when working with chemicals.

**Skin/body protection:**

Impervious gloves (nitrile butyl rubber, neoprene and PVC) should be worn always when working with this product. Body should be covered with appropriate clothing (apron, arm covers or full body suit) depending on the task being performed and the risks involved. Protective clothing should be selected and used in accordance with “Guidelines for the Selection of Chemical Protective Clothing” published by ACGIH. Wash contaminated clothing before reuse. Store work clothing separately. Appropriate footwear should be also selected based on the task being performed and the risks involved.

**Respiratory protection:**

Use local or general ventilation to control exposures below applicable exposure limits. When ventilation is inadequate, use either an atmosphere supplying respirator or NIOSH or OSHA approved air-purifying respirator for organic vapors. Respirator must be properly fitted and its selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Additional Protective Measures:** Educate and train employees in safe handling of this product. Follow all label instructions. As a general hygiene practice, wash hands and face after use. Clean water should always be readily available for emergency skin and eye washing. Emergency eyewash fountains and safety shower are recommended in close proximity as a matter of good work practice.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Black Liquid
<b>Odor:</b>	Slightly ammonia-like
<b>Odor threshold:</b>	Not available
<b>pH:</b>	8 – 10
<b>Melting point/ freezing point:</b>	Not available
<b>Initial boiling point and boiling range:</b>	>200°C
<b>Flash point:</b>	>200°C
<b>Evaporation rate:</b>	Not applicable
<b>Flammability (solid, gas):</b>	Not applicable
<b>Upper/ lower flammability or explosive limits:</b>	Not applicable
<b>Vapor pressure:</b>	Negligible
<b>Vapor density:</b>	Not available
<b>Relative density:</b>	1.00-1.05 @ 25°C (77°F)
<b>Solubility (water):</b>	Very slightly soluble
<b>Partition coefficient n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	>250°C
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**SECTION 10 – STABILITY AND REACTIVITY**

**Reactivity:** Product will not undergo hazardous polymerization. Corrosive effects to metal are not anticipated. Based on its structural properties the product is not classified as oxidizing. Does not form flammable gases in the presence of water.

**Chemical stability:** Stable under recommended storage conditions. Product is hygroscopic; contamination with moisture will negatively affect product performance. Avoid unintended contact with isocyanates; the reaction will generate heat.

**Conditions to avoid:** Unintentional contact with moisture, excessive heat, open flame and sparks. Avoid mist formation.

**Incompatible materials:** Strong oxidizing agents. Water, alcohols, amines, bases, acids, copper, aluminum and zinc alloys.

**Hazardous decomposition products:** Depend upon temperature, air supply and presence of other materials. Can include, but are not limited to carbon and nitrogen oxides, amines, hydrogen cyanide, lower molecular weight organic molecules.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

**Likely Routes of Exposure:** Skin and Eye Contact, Inhalation and Ingestion.

**Symptoms of exposure:**

**Acute toxicity:**

**Oral:**

Harmful if swallowed. May cause burns to mouth, throat and stomach. Adverse symptoms may include abdominal pain, nausea, vomiting, and diarrhea.

**Dermal:**

May be harmful in contact with skin. Adverse symptoms may include irritation and redness.

**Inhalation:**

Inhalation is unlikely due to the low vapor pressure. However, if handled at elevated temperatures, it may give off-gas, vapor or mist that is very irritating to the respiratory system. Adverse symptoms may include nausea, headache, difficulties with breathing.

- DETDA, CAS #: 68479-98-1: Inhalation, skin absorption or ingestion may cause methemoglobin formation resulting in a reduced ability of the blood to carry oxygen; a symptom may include cyanosis (purplish-blue coloring of the skin, fingernails, and lips).

**Skin corrosion / irritation:**

Causes skin irritation if not washed off accordingly. Adverse symptoms may include irritation and redness.

**Serious eye damage / eye irritation:**

May cause serious eye irritation. Adverse symptoms may include tearing and redness.

**Specific target organ toxicity, single exposure:**

Not classified.

**Aspiration hazard:**

Not an aspiration hazard.

**Chronic toxicity:**
**Respiratory and Skin Sensitizer:**

Not classified.

**Germ cell mutagenicity:**

Not classified.

**Carcinogenicity:**

This product contains component reported to be possibly carcinogenic to humans by IARC.

- Carbon Black, CAS #: 1333-86-4: IARC: Group 2B (Possibly Carcinogenic to Humans)
- Zeolites, CAS #: 1318-02-1: IARC: Group 3 (Not Classifiable as to its Carcinogenicity to Humans)

Negative effects of Carbon Black on health are minimized, considering that it is dispersed in liquid. However, precautions should be taken to avoid breathing mists created by heating, mixing or spraying and dust from cutting or grinding of cured product containing this component.

**Reproductive toxicity:**

Not classified.

**Specific target organ toxicity, repeated exposure:**

Liver, kidney, pancreas, respiratory system/lungs.

**Medical conditions aggravated by overexposure:**

Liver, kidney, pancreas, respiratory system/lungs and skin disorders if product is handled without adequate protection.

**Toxicity test results:** Not available for mixture. Results for components:

Components	Test Results
Rhino Poly 170™ CAS #: Proprietary	No test data available on the component.
Diethyltoluenediamine (DETDA) CAS #: 68479-98-1	<p><u>Acute Toxicity</u>            Oral LD50 (Rat): 738 mg/kg (OECD Test Guideline 401)            Dermal LD50 (Rat): &gt;2,000 mg/kg (OECD Test Guideline 402)            Skin corrosion/irritation (Rabbit): Non-irritating (OECD Test Guideline 404)            Eye Irritation (Rabbit): Irritating (US-EPA)</p> <p><u>Chronic Toxicity</u>            Skin Sensitization (guinea pig): Negative (intracutaneous test)            Germ cell mutagenicity: Positive and negative results were seen in various in Vitro and in Vivo studies.            Reproductive toxicity: Oral (Rat, females), Dose: 0, 50, 150, 500 mg/kg            General Toxicity Maternal: No observed adverse effect level: 50 mg/kg body weight            Teratogenicity: No observed adverse effect level: 500 mg/kg body weight            Embryo-fetal toxicity: No observed adverse effect level: 150 mg/kg body weight            Embryotoxic effects and adverse effects on the offspring were detected only at high maternally toxic doses (OECD Test Guideline 414)            STOT, RE: Oral (Rat), 90 days, Dose: 50-125-320ppm, NOEL: ≥8 mg/kg; LOEL: ≥21 mg/kg; Dermal (Rabbit), 21 day, Dose: 1-10-100mg/kg, NOEL: ≥10 mg/kg            Chronic ingestion may cause liver damage. Pancreas damage.</p>
Polycaprolactone triol CAS #: 37625-56-2	<p><u>Acute Toxicity</u>            LD50 Oral - Rat - male and female - &gt; 2,000 mg/kg (Directive 67/548/EEC, Annex V, B.1.)            Inhalation: No data available            Dermal: No data available            Skin corrosion/irritation: Skin – Rabbit Result: No skin irritation - 4 h (OECD Test Guideline 404)            Serious eye damage/eye irritation: Eyes – Rabbit Result: No eye irritation (OECD Test Guideline 405)</p> <p><u>Chronic Toxicity</u>            Respiratory or skin sensitisation: Mouse Result: Does not cause skin sensitisation. (OECD Test Guideline 429)            Germ cell mutagenicity: Ames test S. typhimurium Result: negative            Carcinogenicity: Not classified.            STOT-SE: No data available.</p>

	STOT-RE: No data available.
2,2',2''-nitrotriethanol CAS #: 102-71-6	Acute Toxicity: Not expected to cause adverse acute health effects. Chronic Toxicity: Not expected to cause adverse chronic health effects.
Zeolites CAS #: 1318-02-1	<p><u>Acute Toxicity</u> Oral LD50 (Rat): &gt;5,110 mg/kg (OECD Guideline 401); May cause gastrointestinal tract irritation. Dermal LD50 (Rabbit): Not data available Inhalation LC50 (Rat)(dust/aerosol), 4hrs : &gt;5.3 mg/L. Slightly irritant. Skin corrosion/irritation (Rabbit): Slightly irritant. May cause dehydration. Serious eye damage/eye irritation (Rabbit): Slightly irritant. May cause abrasion or mechanical irritation. STOT, SE: risk to humans is not expected from exposure to this product. Aspiration hazard: No</p> <p><u>Chronic toxicity</u> Sensitization, skin and respiratory: Not sensitizer (Guinea pig maximization test) Germ cell mutagenicity: Risk to humans is not expected from exposure to this product. Carcinogenicity: IARC: Group 3 (Not Classifiable as to its Carcinogenicity to Humans) Reproductive toxicity: No adverse effects in rats and rabbits or their offspring following administration in the drinking water during pregnancy. STOT, RE: Effects on kidney were observed in rats and dogs administered high dose levels in their feed for one month. Effect on blood, chronic pneumonitis and acute bronchopneumonia were observed in dogs. Long-term inhalation by rats and dogs produced inflammation in the lungs associated with accumulation of particulate.</p>
Carbon Black CAS #: 1333-86-4	<p><u>Acute Toxicity</u> Oral LD50 (Rat): &gt;8,000 mg/kg; Carbon Black is inert, insoluble and is not expected to present an ingestion hazard Skin corrosion/irritation (Rabbit): non- irritating, index score 0.6/8 (4 = severe edema) Eye irritation (Rabbit): non-irritating, Draize score 10-17/110 (100 maximally irritating)</p> <p><u>Chronic toxicity:</u> Germ cell mutagenicity: In Vitro: not suitable to be tested in bacterial (Ames test) and other in-vitro systems because of its insolubility. When tested, however, results for carbon black showed no mutagenic effects. Organic solvent extracts of carbon black can, however, contain traces of polycyclic aromatic hydrocarbons (PAHs). A study to examine the bioavailability of these PAHs showed that PAHs are very tightly bound to carbon black and not bioavailable. / In Vivo - In an experimental investigation, mutational changes in the hprt gene were reported in alveolar epithelial cells in the rat following inhalation exposure to carbon black. This observation is believed to be rat specific and a consequence of "lung overload" which led to chronic inflammation and release of oxygen species. This is thus considered to be a secondary genotoxic effect and thus carbon black itself would not be considered to be mutagenic. Carcinogenicity: IARC: Group 2B: Tumor development in rats caused by lung overload. No epidemiological evidence for lung tumors in humans. Lung tumors in rats are the result of exposure under "lung overload" conditions. The development of lung tumors in rats is specific to this species. Mouse and hamster do not develop lung tumors under similar test conditions. The European CLP guidance on classification and labelling states, that „lung overload“ in animals is listed under mechanism not relevant to humans and that no classification is necessary if the mechanism is not relevant to humans. ACGIH: Group A4 - Not classifiable as a human carcinogen. NIOSH: 1978 criteria document on carbon black recommends that only carbon blacks with PAH contaminant levels greater than 0.1% require the measurement of PAHs in air. As some PAHs are possible human carcinogens, NIOSH recommends an exposure limit of 0.1 mg/m<sup>3</sup> for PAHs in air, measured as the cyclohexane-extractable fraction. Not listed as a human carcinogen by NTP and OSHA. Inhalation (Rat/Mouse), 2 years, Target organ: lungs; Effect: inflammation, fibrosis, tumors; Oral (Rat), 2 years: no tumors; Oral (Mouse), 2 years: no tumors; Dermal (Mouse), 1.5 years: no skin tumors; Inhalation (Mouse/hamster), 1-2 years Target organ: lungs: no tumors; Inhalation (Rat), 2 years Target organ: lungs: inflammation, fibrosis, tumors. Reproductive toxicity: No experimental studies are available. However, based on toxicokinetic data, carbon black is deposited in the lungs and based on its specific physicochemical properties (insolubility, low absorption potential), it is not likely to distribute in the body to reach reproductive organs, embryo and/or fetus under in vivo conditions. Therefore, no adverse effects to fertility/reproduction or to fetal development are expected. STOT, RE: Inhalation (Rat), 90 days, Target organ: lungs, NOAEL = 1.1 mg/m<sup>3</sup> (respirable)-Effect: inflammation, hyperplasia, fibrosis; Prolonged or repeated inhalation of dust may cause pulmonary fibrosis or emphysema. Inhalation studies with the rat showed lung effects. These effects are believed to be the effects of "lung overload" and specific to the species.</p>

***The products in question have been evaluated against the Hazardous Products Regulations (WHMIS 2015) and no additional classifications, ingredient disclosure or exposure limits are required for those regulations.***

**SECTION 12 – ECOLOGICAL INFORMATION**
**Ecotoxicity:**

Acutely and chronically hazardous for aquatic organisms. Do not release into natural waters.

**Persistence and degradability:**

Not readily biodegradable by OECD criteria. In contact with water the substance will hydrolyze slowly.

**Bioaccumulative potential:**

No significant accumulation in organisms is expected.

**Mobility in soil:**

Not known.

**Other adverse effects:**

Not known.

**Ecotoxicity test results:** Not available for the mixture. Results for components:

Components	Test Results
Rhino Poly 170™ CAS #: Proprietary	No test data available on the component.
Diethyltoluenediamine (DETDA) CAS #: 68479-98-1	<p>Aquatic Summary: Very toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment.</p> <p><u>Acute Toxicity</u>            Fish: LC50 (Fathead minnow), 96hrs: &gt;106 mg/L (OECD Guideline 203)            Aquatic Invertebrates: EC50 (Daphnia magna), 48hrs: 5.8 mg/L (OECD Guideline 202)            Algae: ErC50 (Green algae), 72hrs: 104 mg/L (OECD Guideline 201)</p> <p><u>Ecological Data</u>            Microorganisms, EC50 (bacterium), 24hrs: &gt;170 mg/L (DIN 38412 Part 8)            Biodegradation, 28days: &lt;1 % (OECD Guideline 301D); COD: 2,370 mg/g</p>
Polycaprolactone triol CAS #: 37625-56-2	Fish semi-static test LC50 - Danio rerio (zebra fish) - 150 mg/l - 96 h (OECD Test Guideline 203)
2,2',2"-nitritriethanol CAS #: 102-71-6	No test data available on the component.
Zeolites CAS #: 1318-02-1	<p><u>Acute Toxicity:</u>            Fish (fathead minnow), 96hrs: LC50: &gt;680 mg/L (EPA 72-1, static). The details of the toxic effect relate to the nominal concentration. The LC50 is higher than the solubility limit.            Aquatic invertebrates (Daphnia magna), 24hrs: EC50: 2,808 mg/L (OECD Test Guideline 202, part 1, static)            Aquatic plants (Green algae), 96hrs: EC50: &gt;328 mg/L (OECD Test Guideline 201, static). The details of the toxic effect relate to the nominal concentration. Tested above maximum solubility. The product has low solubility in the test medium. An eluate has been tested.            Microorganisms (Bacteria), 16hrs: EC50: 950 mg/L (Growth inhibition) (DIN 38412, Part 8). The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An eluate has been tested.</p> <p><u>Chronic toxicity:</u>            Fish (fathead minnow), 30days: NOEC: ≥86.7 mg/L (OPP 72-5, EPA-Guideline, Flow through). The statement of the toxic effect relates to the analytically determined concentration.            Aquatic invertebrates (Daphnia magna), 21days: NOEC: 32 mg/L (OECD Test Guideline 211, semistatic). The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An eluate has been tested.</p> <p><u>Ecological Data:</u>            Biodegradability: Not readily biodegradable. The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants. It cannot be eliminated from water by biological purification processes.            Mobility in soil: Transport between environmental compartments: Study scientifically not justified.</p>
Carbon Black CAS #: 1333-86-4	<p><u>Acute toxicity</u>            Fish: LC50 (Zebra fish), 96hrs (OECD Test Guideline 203): &gt;1,000 mg/L            Aquatic invertebrates: EC50 (Daphnia magna), 24hrs (OECD Test Guideline 202): &gt;5,600 mg/L            Aquatic plants: EC50 (Algae), 72hrs (OECD Test Guideline 201): &gt;10,000mg/L; NOEC 50: &gt;10,000 mg/L</p> <p><u>Ecological Data</u></p>



Activated sludge, EC0, 3hrs (TTC test, DEV L3): 800 mg/L  
Persistence and degradability: Effects are not expected due to its stability and insolubility in water or organic solvents. Carbon black is inert elemental carbon and cannot be further biodegraded by microorganisms, hydrolysis, photo-degradation in air or in surface water.  
Bioaccumulative potential: No significant accumulation in organisms is expected. Not expected to occur in air or water in relevant amounts due to stability, insolubility and low vapor pressure. The deposition in soil or sediments is the most possible fate in the environment.

**SECTION 13 – DISPOSAL CONSIDERATIONS**

**Product Disposal:** The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

**Container disposal:** Even after emptying, container may retain residues. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation. This material and its container must be disposed of in a safe way.

**SECTION 14 – TRANSPORT INFORMATION****DOT**

Not regulated as dangerous goods.

**IATA**

Not regulated as dangerous goods.

**IMDG**

Not regulated as dangerous goods.

**BULK TRANSPORT**

according to Annex II or MARPOL 73/78 and IBC Code

Not available

**SECTION 15 – REGULATORY INFORMATION****U.S. Regulations:**

**OSHA HCS:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29CFR 1910.1200.

**TSCA Regulations:**

All components of this product are listed or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**EPCRA Section 302 (40 CFR Part 355)** (Emergency Response Planning, Extremely Hazardous Substance):

No components are subject to the reporting.

**EPCRA Section 304 (40 CFR Part 355)** (Emergency Release Notification Requirements):

No components are subject to the reporting.

**EPCRA Sections 311 & 312** (Hazardous Chemical Inventory Reporting, Hazard Categories):

Acute Health Hazard, Chronic Health Hazard

**EPCRA Section 313 (40 CFR Part 372)** (Toxic Chemical Release Inventory Reporting):

No components are subject to the reporting.

**CERCLA Sections 102-103 (40 CFR Part 302)** (Hazardous Substances Release Notification):

No components are subject to the reporting.

**Clean Air Act:**

- Ozone Depleting Substances (ODS): This product does not contain and is not manufactured with ozone depleting substances.
- Hazardous Air Pollutants, OSHA, Section 112(b), Table Z-1: The following components are listed: See Section 8.

**Clean Water Act:**

- Section 307(a) (Toxic pollutants): No components are listed.
- Section 311(b)(2): Table 116.4A (Hazardous chemicals) / Table 117.3 (RQ): No components are listed.

**NFPA rating:** Health: 2 Fire: 1 Reactivity: 1 Special: 0**HMIS rating:** Health: 2 Flammability: 1 Physical hazard: 1

Rating: 0 – Minimal | 1 – Slight | 2 – Moderate | 3 – Serious – 4 – Severe

**State Regulations:**

California Prop. 65 Components:



**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

No components are subject to the reporting.

**Canada regulations/legislation:**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

**International Regulations/Inventories:**

No data available.

**SECTION 16 – OTHER INFORMATION****LEGEND**

GHS	Globally Harmonized System
CAS	Chemical Abstracts Services
EC	European Community
EPA	Environmental Protection Agency
OSHA	Occupational Safety and Health Administration
ACGIH	American Conference of Governmental Industrial Hygienists
NIOSH	National Institute of Occupational Safety and Health
PEL	Permissible Exposure Limits
TLV	Threshold Limit Value
REL	Recommended Exposure Limit
TWA	Time-Weighted Average
STEL	Short-term exposure limit
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
COD / BOD	Chemical Oxygen Demand / Biological Oxygen Demand
STOT, SE	Specific Target Organ Toxicity following Single Exposure
STOT, RE	Specific Target Organ Toxicity following Repeated Exposure
DOT	Department of Transportation
IMDG	International maritime dangerous goods code
IATA, ICAO	International Air Transport Association, International Civil Aviation Organization
TSCA	Toxic Substances Control Act
EPCRA	Emergency Planning and Community Right-to-Know Act
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
CFR	Code of Federal Regulations
RQ	Reportable Quantity
EHS	Extremely Hazardous Substances
DSL	Domestic Substance List



## SAFETY DATA SHEET

Part No.: 60296

Date: November 27, 2019

WHMIS Workplace Hazardous Materials Information System

**Latest revision date:** November 27, 2019

**Date of the previous revision:** New Product

**Disclaimer:** The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. **Rhino Linings Corporation** makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.