

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

SECTION 1 - IDENTIFICATION

Manufacturer's Info: Rhino Linings Corporation 9747 Businesspark Avenue San Diego, CA 92131 Product name: Product Category: Recommended use: ThermalGuard OC 0.5P, Part B Polyurethane Resin Blend For 2 component SPF

Information phone: (858) 450 0441

Emergency contact: CHEMTREC (800) 424 9300

SECTION 2 - HAZARD(S) IDENTIFICATION

OSHA Hazard Communication Standard:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

GHS-Label Elements:

Signal Word: DANGER

Pictogram(s):





GHS 05

GHS 08

Classification of the substance or mixture:

Hazard Class	Category	Hazard Statement Codes	Hazard Statements
Acute Toxicity, Oral	4	H302	Harmful if swallowed
Acute Toxicity, Dermal	5	H313	May be Harmful in contact with skin
Skin corrosion / irritation	1A-1C	H314	Causes severe skin burns and eye damage.
Serious eye damage / Eye irritation	2B	H320	Causes eye irritation.

Precautionary Statements:

Prevention:	P280	Wear protective gloves/ protective clothing / eye protection/ face protection.
	P264	Wash exposed area with plenty of water and soap thoroughly after handling.
	P270	Do not eat, drink, and smoke when using this product.
	P260	Do not breathe mist, vapors, spray.
	P273	Avoid release to the environment.
Response:	P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303 + P361 + P352	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
		Wash with plenty of soap and water.
	P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for
		breathing.
	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	P310	i j
		,
		•
	P363	
Storage:	P405	<u> </u>
Disposal:	P501	Dispose of contents/container to hazardous or special waste collection point.
Storage: Disposal:	P310 P314 P332 + P313 P363 P405	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact ler present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Store locked up.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS#	EINECS #	Concentration, %
Halogenated Phosphate	Trade Secret	N/A	15 – 35%
Amine Catalyst Blend	Trade Secret	N/A	3 – 10%

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

SECTION 4 - FIRST-AID MEASURES

Description of First Aid measures:

Inhalation: Immediate medical attention required. Call a poison center or physician. Remove victim to fresh air and keep at

rest in a position comfortable for breathing.

If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person should be kept under medical surveillance for 48 hours.

Skin: Immediate medical attention required. Call a poison center or physician. Chemical burns must be treated

promptly by a physician or dermatologist. Wash material off of the skin with plenty of soap and water for at least

15 minutes.

Remove contaminated clothing and shoes immediately and wash them before reuse.

Eye: Immediate medical attention required. Call a poison center or physician. Chemical burns must be treated

promptly by a physician or ophthalmologist.

Rinse cautiously with water for several minutes, especially under the eyelids. Remove contact lenses, if present

and easy to do. Continue rinsing for at least 15 minutes. Do not rub eyes in order to prevent cornea injury.

Ingestion: Immediate medical attention required. Call a poison center or physician. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. Remove dentures if any.

If the exposed person is conscious, rinse mouth with water and then give plenty of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that

vomit does not enter the lungs. Do not induce vomiting unless directed to do so by medical personnel.

If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Never induce vomiting or give anything by mouth if

the victim is unconscious or having convulsions.

Most important symptoms/effects, acute and delayed:

See Section 11.

General advice for First Aid responders:

No action should be taken involving any personal risk or without suitable training. If potential for exposure exist refer to Section 8 for specific personal protective equipment. Show this SDS to physician.

Note to physician: Antidote: Specific antidotes or neutralizers do not exist. Treatment should be supportive and based on the judgment of the physician in response to the reaction of the patient. Recommended medical monitoring for at least 24 hours.

SECTION 5 - FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray, alcohol-resistant foam, dry chemical or carbon dioxide fire extinguishers.

Unsuitable extinguishing media: Direct water stream may cause frothing, splattering of burning material and spreading of fire.

Specific hazards arising from the chemical: Material may be ignited only if preheated to high temperatures (such in fire conditions). Fire in vicinity poses risk of pressure build-up and rupture. Containers at risk from fire should be cooled with water and, if possible, removed from the danger area. Hazardous Combustion products: Carbon dioxide, Carbon monoxide, nitrogen oxides, lower molecular weight organic molecules.

Special Protective Equipment and Precautions for fire-fighters: Wear NIOSH or OSHA approved self-contained breathing apparatus in positive pressure mode with full face piece and full protective gear. Isolate the scene by removing all persons from the incident area. No action should be taken involving any personal risk or without suitable training. Spilled product will cause very slippery walking surfaces.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training.

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

Keep unnecessary and unprotected personnel from entering. Ensure adequate ventilation/exhaust extraction. Avoid breathing vapors or mist during clean up. Use protective equipment as described in Section 8. Do not touch or walk through spilled material; spilled material may cause a slipping hazard.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Inform the relevant authorities if the product has caused environmental pollution. Water polluting material. May be harmful to the environment if released in large quantities. See Section 12.

Methods and materials for containment and cleaning up: Remove mechanically; cover the remainder with non-combustible absorbent material (e.g. sawdust, sand, earth, vermiculite or diatomaceous earth). After approximately one hour, transfer into properly labeled chemical waste containers. Cover container, but do not seal, and remove from work area. Keep in a well ventilated area. Wash the spill site with soap and water.

For major spills: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or contain and collect with an absorbent material as described in the previous paragraph.

Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, see Section 1 for the Emergency contact; for further disposal measures, see Section 13.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling: Protect chemical from atmospheric moisture. Avoid prolonged exposure to heat and air. Keep away from sources of ignition. Do not reseal if contamination is suspected.

Use adequate ventilation to keep airborne levels below the exposure limits. Do not breathe vapors and mists. Wear respiratory protection if material is heated, mixed, sprayed or used in a confined space. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash hands thoroughly after handling. Hands and/or face should be washed before eating, drinking and smoking and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities: Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect it against physical damage and moisture. Normal temperature and pressures do not affect the material. Keep liquid away from heat, sparks and flame. Do not cut, drill, grind, weld or perform similar operations on or near containers. Use appropriate containment to avoid environmental contamination.

Storage stability: Stable under normal conditions. Storage temperature: 60 - 90°F (16 - 32°C)

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200. Employees and consumers should be warned of health risks associated with product use.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters/Occupational exposure limit values: Not available for mixture. Results for components: USA

Components	CAS#	OSHA PEL	ACGIH TLV	NIOSH
Halogenated Phosphate	Trade Secret	No data	No data	No data
Amine Catalyst Blend	Trade Secret	No data	TLV: 0.05 ppm STEL: 0.15 ppm	No data

Appropriate engineering controls: Good local and general ventilation should be sufficient to control worker exposure to airborne contaminants below recommended exposure limits. Local exhaust may be required in some areas.

Personal protective equipment:

Eye/face protection:

When directly handling liquid product, eye protection is required. Examples of eye protection include safety glasses and goggles or full face shield when there is a greater risk of splash. Contact lenses should not be worn when working with chemicals.

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

Skin/body protection:

Avoid contact with skin. Impervious gloves (nitrile butyl rubber, neoprene and PVC) should be worn always when working with this product. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact. Dispose contaminated gloves after use in accordance with good laboratory practices. Body should be covered with appropriate clothing (apron, arm covers or full body suit) depending on the task being performed and the risks involved. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH. Wash contaminated clothing before reuse. Store work clothing separately. Appropriate footwear should be also selected based on the task being performed and the risks involved.

Respiratory protection:

Use local or general ventilation to control exposures below applicable exposure limits. When ventilation is inadequate, use either an atmosphere supplying respirator or NIOSH or OSHA approved air-purifying respirator for organic vapors. Respirator must be properly fitted and its selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Additional Protective Measures: Educate and train employees in safe handling of this product. Follow all label instructions. As a general hygiene practice, wash hands and face after use. Emergency eyewash fountains and safety shower should be in close proximity as a matter of good practice.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Amber Liquid
Odor:	Ammonia-like
Odor threshold:	Not available.
pH:	10
Melting point/ freezing point:	< - 30°C (<-22°F) becomes highly viscous at low temperatures
Initial boiling point and boiling range:	Decomposed before boiling
Flash point:	Closed cup: >185°C (365°F)
Evaporation rate:	Negligible
Flammability (solid, gas):	Not available
Upper/ lower flammability or explosive limits:	Not available
Vapor pressure:	Not available
Vapor density:	Not available
Relative density:	1.09 @ 25°C (77°F)
Solubility (water):	partially soluble
Partition coefficient n-octanol/water:	Not available
Auto-ignition temperature:	>200°C (392°F)
Decomposition temperature:	>200°C (392°F)
Viscosity:	200 - 400 cP @ 25°C (77°F)

^{*}Where data are not known for mixture, they are stated for components, if available.

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Corrosion to metals: Corrosive effects to metal are not anticipated.

Oxidizing properties: Based on its structural properties the product is not classified as oxidizing.

Formation of flammable gases: Does not form flammable gases in the presence of water.

Chemical stability: Stable under recommended storage conditions. Product is hygroscopic; contamination with moisture will negatively affect product performance. Avoid unintended contact with isocyanates; the reaction will generate heat.

Conditions to avoid: Unintentional contact with moisture, excessive heat, open flame and sparks. Avoid mist formation.

Incompatible materials: Strong oxidizing agents. Hazardous decomposition products: Depend upon temperature, air supply and presence of other materials. Can include, but are not limited to carbon dioxide, carbon monoxide, alcohols, ethers, ketones, hydrocarbons, polymer fragments.

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Ingestion, Skin and Eye Contact, Inhalation.

Symptoms of exposure:

Acute toxicity:

Oral: Harmful if swallowed. May cause burns to mouth, throat and stomach. Adverse symptoms may include stomach pain.

Dermal: Causes severe burns. Adverse symptoms may include pain or irritation, redness, blistering.

Inhalation: May give off-gas, vapor or mist that is very irritating or corrosive to the respiratory system.

Skin corrosion / irritation:

Corrosive! Damages skin if not removed immediately. A more severe response may be expected if skin is abraded (scratched or cut).

Serious eye damage / eye irritation:

May cause serious eye damage. Adverse symptoms may include pain, watering, redness.

Aspiration hazard:

Based on physical properties, not likely to be an aspiration hazard.

Chronic toxicity:

Respiratory and Skin Sensitizer:

The chemical structure does not suggest a sensitizing effect. This material is not known or reported to be a skin or respiratory sensitizer.

Germ cell mutagenicity:

Developmental risk to humans is not expected from exposure to this product. Not known or reported to be mutagenic.

Mutagenic effect was not found in various tests with mammalian cell culture and mammals. The substance was not mutagenic in bacteria. No experimental evidence is available for mutagenicity in vitro (Ames test negative).

Carcinogenicity:

This product does not contain ingredients known or reported to be carcinogenic by any reference IARC, NTP, EPA, OSHA, ACGIH.

Reproductive toxicity:

Risk to humans is not expected from exposure to this product. Not known or reported to cause reproductive toxicity.

Specific target organ toxicity, single exposure:

Not expected.

Specific target organ toxicity, repeated exposure:

Respiratory system, lungs

Medical conditions aggravated by overexposure:

Asthma, respiratory disorders if product is handled without adequate protection.

Toxicity test results:

Acute toxicity, LD50, Oral, Rat, 3600. MG/KG.

Results: Behavioral: Somnolence (general depressed activity).

Behavioral: Tremor.

Lungs, Thorax, or Respiration: Other changes.

- National Technical Information Service, Vol/p/yr: OTS05, 7713

Acute toxicity, LD50, Intravenous, Mouse, 56.00 MG/KG.

Results: Behavioral: Food intake (animal).

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- U.S. Army Armament Research & Development Command, Chemical Systems

Laboratory, NIOSH Exchange Chemicals., Aberdeen Proving Ground,

Aberdeen Proving Ground, MD 21010, Vol/p/yr: NX#, 5768

Skin corrosion/irritation, Skin sensitization, Skin, Rabbit, 0.000, Mild.

Results: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Eye:Lacrimation.

Behavioral: Tremor.

Lungs, Thorax, or Respiration: Cyanosis.

Irritation or Corrosion

Skin - rabbit - Mild skin irritation - 24 h.

Serious eye damage/eye irritation:

Skin - rabbit - Corrosive.

Eyes - rabbit - Severe eye irritation.

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

SECTION 12 - ECOLOGICAL INFORMATION

Assessment of aquatic toxicity: Not tested. Do not discharge product into the environment.

Assessment of terrestrial toxicity: Study not necessary due to exposure considerations.

Persistence and degradability: Not readily biodegradable by OECD criteria. In contact with water the substance will hydrolyze slowly.

Bioaccumulative potential: No significant accumulation in organisms is expected.

Mobility in soil: Not expected.

Other adverse effects: No known significant effects or critical hazards.

SECTION 13 - DISPOSAL CONSIDERATIONS

Product Disposal: The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

Container disposal: Even after emptying, container may retain residues. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation.

This material and its container must be disposed of in a safe way.

SECTION 14 - TRANSPORT INFORMATION

Land Transport (US DOT):

Land Transport (Canadian TDG):

Land Transport (European ADR/RID):

Marine Transport (IMDG/IMO):

Air Transport (ICAO/IATA):

Not Regulated.

Not Regulated.

Not Regulated.

SECTION 15 - REGULATORY INFORMATION

NFPA rating: Health: 1 Fire: 0 Reactivity: 0 Special: 0 **HMIS rating:** Health: 1 Flammability: 0 Physical hazard: 0

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S.301 (EHS)	S. 304 RQ	S. 313 (TRI)
Trade Secret	Halogenated Phosphate	No	No	No
Trade Secret	Amine Catalyst	No	No	No

CAS#	Hazardous Components	Other US EPA or State Lists
Trade Secret	Halogenated Phosphate	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
Trade Secret	Amine Catalyst	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: Yes

CAS#	Hazardous Components	International Regulatory Lists
Trade Secret	Halogenated Phosphate	Canadian DSL: YES; Canadian NDSL: NO
Trade Secret	Amine Catalyst	Canadian DSL: YES; Canadian NDSL: NO

Part No.: PUOC(0.5)P Pt. B

Released: May 20, 2015

PRODUCT NAME(S): ThermalGuard OC 0.5P, B Component

Other Regulatory Information: This product contains no chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 40CFR part 372.

European Union Regulations: All ingredients of this product are listed or exempted.

Symbol - none required.

International Regulations/Inventories:

Australia (AICS): All components are listed or exempted. China (IECSC): All components are listed or exempted.

Japan: All components are listed or exempted. Korea: All components are listed or exempted. Malaysia (EHS Register): Not determined.

New Zealand (NZIoC): All components are listed or exempted. Philippines (PICCS): All components are listed or exempted.

Brazil Regulations: Classification system Norma ABNT-NBR 14725-2:2012

SECTION 16 - OTHER INFORMATION

LEGEND

GHS Globally harmonized System CAS **Chemical Abstracts Services Environmental Protection Agency** EPA

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety and Health

Permissible Exposure Limits PEL TLV Threshold Limit Value

REL Recommended Exposure Limit Time-Weighted Average TWA Short-term exposure limit STEL Occupational exposure standard OES

MAK Maximale Arbeitsplatz-Konzentration (maximum workplace concentration)

Technische Regeln fur Gefahrstoffe (regulatory limits) **TRGS**

International Agency for Research on Cancer **IARC**

NTP National Toxicology Program DOT Department of Transportation

IMDG International maritime dangerous goods code

IATA, ICAO International Air Transport Association, International Civil Aviation Organization

EPCRA Emergency Planning and Community Right-to-Know Act

State Authorization Reciprocity Agreements SARA Workplace Hazardous Materials Information System WHMIS

Transport of Dangerous Goods **TDG** Hazard Communication Standard **HCS** Center for European Policy Agreements **CEPA**

EINECS European Inventory of Existing Commercial Chemical Substances

CPR Controlled Products Regulations Polycyclic Aromatic Compounds **PACs**

PAH Polycyclic Aromatic Hydrocarbon Content

SPF Spray Polyurethane Foam

Latest revision date: May 20, 2015 - Preparation of SDS in accordance to the GHS requirements Date of the previous revision:

Disclaimer: The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Rhino Linings Corporation makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.