



Why re-roof when you can restore?

An economical and reliable roofing solution, featuring DuraTite® silicones.

Extend the service life of a new or existing roof with significant energy savings. Rhino Linings® roof restoration system offers:

- DuraTite® silicone coatings are single component, moisture cured products that can be roll or spray applied. DuraTite Silicone coatings may be installed directly onto most existing roof substrates or in conjunction with SPF*. DuraTite silicone coatings extend the life of an existing roof up to 20 years**.
- DuraTite silicone coatings are tested and listed with CRRC (Cool Roof Rating Council) and meet Energy Star and California Title 24 requirements. DuraTite silicone coatings can save building owners up to 15% of their cooling energy costs and significantly reduce solar heat gain.
- Silicone coatings offer resistance to the elements, even when exposed to extreme temperatures, UV radiation, rain and snow. Hot or cold, they retain their elasticity and reflectivity.
- DuraTite 1395 is a high solids, solvent free formulation that can be used in California's Air Quality Management districts as well as other VOC regulated states.



An excellent choice for roof restoration and renewal purposes

A Low Cost, Reliable Roofing System

DuraTite® silicone coatings offer a long term and cost effective solution for repairing worn and failing roofs. Coating by itself cannot salvage a roof that is too far gone, but installed at the right time will maintain the integrity of an existing roof for many years.

DuraTite silicone coatings are classified as maintenance coatings, not a new roof system. This means a building owner can deduct the cost of the coating and installation as a maintenance expense and receive a tax benefit at the end of the year. This is a significant advantage over the requirement that a new roof system be capitalized and depreciated over 20 years or more.

To become a Rhino Linings® applicator or to schedule a roof consultation, call 877.358.1320, or visit spf.rhino linings.com.

You strive to select energy-efficient materials that stand out from the rest. That is why you choose Rhino Linings® products.

In the competitive building industry, you need quality products from a quality company. Silicone coatings by Rhino Linings will save you the money, time and stress of re-roofing.



DuraTite® 1380

DuraTite 1380 is a single component silicone coating that can be applied to both low and steep slope roofing. It provides elemental protection to most roof surfaces including masonry, concrete, metal, single-ply and spray polyurethane foam. DuraTite 1380 forms a breathable membrane while maintaining chemical resistant properties and strong resistance to degradation caused by exposure to the elements. It may be applied in a wide range of ambient temperatures and humidity levels with an airless sprayer, brush, or roller.

Tensile Strength	458 psi @73°F
Elongation	265% @73°F
Tear Resistance	35 lb/in
Shore Hardness	50A
Standard Colors	White, Light Gray, Gray
Solar Reflectance	.66 aged 3 years (white)
Solids (v)	69% ± 2



DuraTite® 1395

DuraTite 1395 is a single-component silicone coating with low VOCs and excellent chemical resistance. When applied, DuraTite 1395 forms a breathable membrane, making it an ideal choice for new and recoat applications over metals, single-ply membranes, modified bitumen, masonry block, concrete, spray polyurethane foam roofing systems and built up roofing. DuraTite 1395 can be applied with a high capacity airless paint sprayer, brush or roller in a wide range of ambient temperatures and humidity levels.

Tensile Strength	486 psi @73°F
Elongation	267% @73°F
Tear Resistance	33.7 lb/in
Shore Hardness	50A
Standard Colors	White, Gray, Tan
Solar Reflectance	.70 aged 3 years (white)
Solids (v)	95% ± 2



FL# 21842



spf.rhino linings.com | 1-877-358-1320

Rhino Linings Corporation | 9747 Businesspark Avenue | San Diego, CA 92131 877.358.1320 | <http://spf.rhino linings.com>

*certain substrates will require a primer for proper adhesion. Adhesion testing is always recommended prior to proceeding with an application.**20 year life expectancy dependent upon application thickness of the coating. Rhino Linings® SPF products are spray polyurethane foams. During application, precautions should be taken by applicators, helpers and building occupants to protect them from fumes, mists and spills. Product information and specifications subject to change without notice. For the most current product information, please consult <http://spf.rhino linings.com>. ©2017 Rhino Linings Corporation. All rights reserved. 7473 0617