Date: August 25, 2021

PRODUCT NAME(S): Pipeliner™ 5000 PW Resin White

SECTION 1 – IDENTIFICATION

Manufacturer's Info: Rhino Linings Corporation 9747 Businesspark Avenue San Diego, CA 92131

Recommended Use:

Product Name:

Pipeliner™ 5000 PW Resin White

For Professional and Industrial Use Only

Information phone: (858) 450 0441

Emergency contact: CHEMTREC (800) 424 9300

SECTION 2 - HAZARD(S) IDENTIFICATION

OSHA Hazard Communication Standard:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

GHS-Label Elements:

Signal Word: WARNING

Pictogram(s):



GHS 08

GHS 07



GHS 0

Classification of the substance or mixture:

Hazard Class	Category	Hazard Statement Codes	Hazard Statements
Acute Toxicity – Oral	5	Н303	May be harmful if swallowed
Skin Corrosion/Irritation	3	H316	Causes mild skin irritation
Serious Eye Damage/Eye Irritation	2A	H319	Causes serious eye irritation
Skin Sensitization	1B	H317	May cause an allergic skin reaction
STOT-RE	2	H373	May cause damage to organs through prolonged or repeated exposure (Kidney, Liver, Pancreas)
Aquatic Hazard – Acute	2	H401	Toxic to aquatic life
Aquatic Hazard – Chronic	2	H411	Toxic to aquatic life with long lasting effects

Precautionary Statements:

Prevention:	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P260	Do not breathe mist, vapors, spray.
	P264	Wash exposed area with plenty of water and soap thoroughly after handling.
	P272	Contaminated work clothing should not be allowed out of the workplace.
	P273	Avoid release to the environment.
	P280	Wear protective gloves, protective clothing, eye protection, face protection.
	P281	Use personal protective equipment as required.



Date: August 25, 2021

Response: P302+P352 **IF ON SKIN:** Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.
P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P391 Collect spillage.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/container to hazardous or special waste collection point in

accordance with local, regional, national, international regulations.

Hazards not otherwise classified (HNOC): Methemoglobin

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS CAS# EC# Concentration, % Components Polyether Polyols Blend 70 - 90Trade Secret **Trade Secret** Diethyltoluenediamine 68479-98-1 270-877-4 10 - 20Zeolites 1318-02-1 930-915-9 1 - 5Titanium Dioxide 0.1 - 213463-67-7 236-675-5 Confidential Component 1 **Trade Secret Trade Secret** 0.1 - 2Confidential Component 2 **Trade Secret Trade Secret** 0.1 - 2

SECTION 4 – FIRST-AID MEASURES

Description of First Aid measures:

Inhalation: Move to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory problems,

seek medical attention.

Skin: Wash material off of the skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing

and shoes immediately and wash them before reuse. Get medical advice/attention if irritation persists.

Eye: Rinse cautiously with water for several minutes, especially under the eyelids. Remove contact lenses, if present

and easy to do. Continue rinsing for at least 15 minutes. Do not rub eyes in order to prevent corneal injury. Get

medical advice/attention if eye irritation persists.

Ingestion: Move to fresh air and keep at rest in a position comfortable for breathing. Remove dentures if any. Rinse mouth

thoroughly with water and then drink 60 to 240 mL (2 to 8 oz). Get medical advice/attention if symptoms occur.

Most important symptoms/effects, acute and delayed: See Section 11 for more details.

General advice for First Aid responders: No action should be taken involving any personal risk or without suitable training. If potential for exposure exist refer to Section 8 for specific personal protective equipment. Show this SDS to physician.

Part No.: 60265W

Date: August 25, 2021

Note to physician: Treatment should be supportive and based on the judgment of the physician in response to the reaction of the patient. Recommended medical monitoring for at least 24 hours.

Diethyltoluenediamine (DETA) may cause methemoglobin formation resulting in a reduced ability of the blood to carry oxygen; a symptom may include cyanosis. Immediately give oxygen if victim turns blue (lips, ears, fingernails). Since reversion of methemoglobin to hemoglobin occurs spontaneously after termination of exposure, moderate degrees of cyanosis need to be treated only by supportive measures.

SECTION 5 - FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray, alcohol-resistant foam, dry chemical or carbon dioxide fire extinguishers.

Unsuitable extinguishing media: Direct water stream may cause frothing, splattering of burning material and spreading of fire.

Specific hazards arising from the chemical: Material may be ignited only if preheated to high temperatures (such in fire conditions). Fire in vicinity poses risk of pressure build-up and rupture. Containers at risk from fire should be cooled with water and, if possible, removed from the danger area. Hazardous combustion products: carbon and nitrogen oxides, amines, hydrogen cyanide, lower molecular weight organic molecules, oxides of metals present in mixture (Section 3).

Special Protective Equipment and Precautions for fire-fighters: Wear NIOSH or OSHA approved self-contained breathing apparatus in positive pressure mode with full face piece and full protective gear. Isolate the scene by removing all persons from the incident area. No action should be taken involving any personal risk or without suitable training. Spilled product will cause very slippery walking surfaces.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Keep unnecessary and unprotected personnel from entering. Ensure adequate ventilation/exhaust extraction. Avoid breathing vapors or mist during clean up. Use protective equipment as described in Section 8. Do not touch or walk through spilled material; spilled material may cause a slipping hazard.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Inform the relevant authorities if the product has caused environmental pollution. Water polluting material. May be harmful to the environment if released in large quantities. See Section 12 for more details.

Methods and materials for containment and cleaning up: Remove mechanically; cover the remainder with non-combustible absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth). Following absorption, transfer into properly labeled chemical waste containers. If necessary, repeat application of absorbent material until all liquid has been removed from the surface. Wash the spill site with soap and water. Cover container and remove from work to a well ventilated area. Properly dispose of the waste material and any contaminated equipment (i.e., broom or brush) in accordance with existing federal, state and local regulations.

For major spills: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Wash spillages into an effluent treatment plant or contain and collect with an absorbent material as described in the previous paragraph.

For minor spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly with soap and water to remove residual contamination. Never return spills to original containers for re-use.

Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, see Section 1 for the Emergency contact; for further disposal measures, see Section 13.

Part No.: 60265W

Date: August 25, 2021

SECTION 7 – HANDLING AND STORAGE

Precautions for safe handling: Protect chemical from atmospheric moisture. Avoid prolonged exposure to heat and air. Keep away from sources of ignition. Do not reseal if contamination is suspected.

Use adequate ventilation to keep airborne levels below the exposure limits. Do not breathe vapors and mists. Wear respiratory protection if material is heated, mixed, sprayed or used in a confined space. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash hands thoroughly after handling. Hands and/or face should be washed before eating, drinking and smoking and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities: Store in original or approved alternative container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect it against physical damage and moisture. Normal temperature and pressures do not affect the material. Keep liquid away from heat, sparks and flame. Do not cut, drill, grind, weld or perform similar operations on or near containers. Use appropriate containment to avoid environmental contamination. Segregate from acids and acid forming substances.

Storage stability: Stable under normal conditions. **Storage temperature:** 60 - 90°F (16 – 32°C)

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200. Employees and consumers should be warned of health risks associated with product use. See Section 8 for additional information on hygiene measures.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters/Occupational exposure limit values: Components listed in the OSHA Occupational Chemical and/or OARS-WEEL Database.

OSHA PEL		NIOSH REL		ACGIH TLV©		Cal/OSHA PEL	
8-hou	r TWA	Up to 10-l	Up to 10-hour TWA 8-hour TWA		r TWA	8-hour TWA	
(ST)	STEL	(ST)	STEL	(ST)	STEL	(ST) STEL	
(C) Ceili	ing Peak	(C) C	eiling	(C) C	eiling	(C) Ceiling Peak	
		TIT	ANIUM DIOXIDE	- CAS # 13463-6	57-7	_	
PEL-TWA	15 mg/m³ (total dust)	REL-TWA		TLV-TWA	10 mg/m³ [1992]	PEL-TWA	10 mg/m³ (total dust) 5 mg/m³ (resp fraction)
PEL-STEL		REL-STEL		TLV-STEL		PEL-STEL	
PEL-C		REL-C		TLV-C		PEL-C	
		IDLH	5000 mg/m³				
Skin Notation	N	Skin Notation	N	Skin Notation	N	Skin Notation	N
<u> </u>	Carcinogenicity classifications: IARC-2B, NIOSH-Ca, TLV-A4						
AIHA emergen	AIHA emergency response planning guidelines - ERPG-1/ERPG-2/ERPG-3:						
AIHA OARS-WE	EEL:						

Date: August 25, 2021

Appropriate engineering controls: Good local and general ventilation should be sufficient to control worker exposure to airborne contaminants below recommended exposure limits. Local exhaust may be required in some areas.

Personal protective equipment:

Eye/face protection:

When directly handling liquid product, eye protection is required. Examples of eye protection include safety glasses and goggles or full face shield when there is a greater risk of splash. Contact lenses should not be worn when working with chemicals.

Skin/body protection:

Impervious gloves (nitrile butyl rubber, neoprene and PVC) should be worn always when working with this product. Body should be covered with appropriate clothing (apron, arm covers or full body suit) depending on the task being performed and the risks involved. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH. Wash contaminated clothing before reuse. Store work clothing separately. Appropriate footwear should be also selected based on the task being performed and the risks involved.

Respiratory protection:

Use local or general ventilation to control exposures below applicable exposure limits. When ventilation is inadequate, use either an atmosphere supplying respirator or NIOSH or OSHA approved air-purifying respirator for organic vapors. Respirator must be properly fitted and its selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Additional Protective Measures: Educate and train employees in safe handling of this product. Follow all label instructions. As a general hygiene practice, wash hands and face after use. Clean water should always be readily available for emergency skin and eye washing. Emergency eyewash fountains and safety shower are recommended in close proximity as a matter of good work practice.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	White Liquid		
Odor:	Slightly ammonia-like		
Odor threshold:	Not available		
pH:	8 – 10		
Melting point/ freezing point:	Not available		
Initial boiling point and boiling range:	>200°C		
Flash point:	>200°C		
Evaporation rate:	Not applicable		
Flammability (solid, gas):	Not applicable		
Upper/ lower flammability or explosive limits:	Not applicable		
Vapor pressure:	Negligible		
Vapor density:	Not available		
Relative density:	1.00-1.10 @ 25°C (77°F)		
Solubility (water):	Very slightly soluble		
Partition coefficient n-octanol/water:	Not available		
Auto-ignition temperature:	>250°C		
Decomposition temperature:	Not available		
Viscosity:	Not available		

Part No.: 60265W

Date: August 25, 2021

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: Product will not undergo hazardous polymerization. Corrosive effects to metal are not anticipated. Based on its structural properties the product is not classified as oxidizing. Does not form flammable gases in the presence of water.

Chemical stability: Stable under recommended storage conditions. Product is hygroscopic; contamination with moisture will negatively affect product performance. Avoid unintended contact with isocyanates; the reaction will generate heat.

Conditions to avoid: Unintentional contact with moisture, excessive heat, open flame and sparks. Avoid mist formation. **Incompatible materials**: Strong oxidizing agents. Water, alcohols, amines, bases, acids, copper, aluminum and zinc alloys.

Hazardous decomposition products: Depend upon temperature, air supply and presence of other materials. Can include, but are not limited to carbon and nitrogen oxides, amines, hydrogen cyanide, lower molecular weight organic molecules, oxides of metals present in mixture (Section 3).

SECTION 11 – TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin and Eye Contact, Inhalation and Ingestion.

Symptoms of exposure:

Acute Toxicity:

Oral:

May be harmful if swallowed.

Adverse symptoms may include abdominal pain, nausea and diarrhea.

Dermal:

Not classified.

Adverse symptoms may include irritation and redness.

Inhalation:

Not classified.

Inhalation is unlikely due to the low vapor pressure. However, if handled at elevated temperatures, it may give off-gas, vapor or mist that is very irritating to the respiratory system. Adverse symptoms may include nausea, headache, difficulties with breathing.

■ DETDA, CAS #: 68479-98-1: Inhalation, skin absorption or ingestion may cause methemoglobin formation resulting in a reduced ability of the blood to carry oxygen; a symptom may include cyanosis (purplish-blue coloring of the skin, fingernails, and lips).

Skin corrosion / irritation:

Causes mild skin irritation.

Adverse symptoms may include irritation and redness.

Serious eye damage / eye irritation:

Causes serious eye irritation.

Adverse symptoms may include tearing and redness.

Specific target organ toxicity, single exposure:

Not classified.

Aspiration hazard:

Not classified.

Date: August 25, 2021

Chronic Toxicity:

Respiratory and Skin Sensitizer:

May cause an allergic skin reaction.

This product contains a component that is reported to be a skin or respiratory sensitizer.

Confidential Component 1, CAS #: Trade secret: skin sensitizer.

Germ cell mutagenicity:

Not classified.

Carcinogenicity:

Not classified.

Reproductive toxicity:

Not Classified.

Specific target organ toxicity, repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Liver, kidney, pancreas, respiratory system/lungs.

Medical conditions aggravated by overexposure:

Liver, kidney, pancreas, respiratory system/lungs and skin disorders if product is handled without adequate protection.

Toxicity test results:

This product itself has not been tested. Information given is based on data on the components and the toxicology of similar products.

Components	Test Results
	Acute Toxicity
	Oral LD50 (Rat): >5,000 mg/kg; may cause mild gastrointestinal effects including nausea and diarrhea
	Dermal LD50 (Rabbit): >2,000 mg/kg
	Inhalation LC50 (Rat), 1hr: >200 mg/L; not expected to cause any significant respiratory tract effects.
	Skin corrosion/irritation (Rabbit): may cause slight irritation, but not expected to cause serious
	damage.
	Serious eye damage/eye irritation (Rabbit): may cause irritation (redness), but not expected to cause
	serious damage.
Polyether Polyols Blend	Aspiration hazard: No
CAS # Trade secret	Chronic Toxicity
	Sensitization, skin and respiratory: Not sensitizer
	Germ cell mutagenicity: Risk to humans is not expected from exposure to this product.
	Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is
	identified as probable, possible or confirmed human carcinogen by IARC, NTP, OSHA and ACGIH.
	Reproductive toxicity: Risk to humans is not expected from exposure to this product.
	STOT-SE: risk to humans is not expected from exposure to this product.
	STOT-RE: No known or reported target organs from repeated exposure.
	Acute Toxicity
	Oral LD50 (Rat): 738 mg/kg (OECD Test Guideline 401)
	Dermal LD50 (Rat): >2,000 mg/kg (OECD Test Guideline 402)
	Skin corrosion/irritation (Rabbit): Non-irritating (OECD Test Guideline 404)
	Eye Irritation (Rabbit): Irritating (US-EPA)
	<u>Chronic Toxicity</u>
	Skin Sensitization (guinea pig): Negative (intracutaneous test)
Diethyltoluenediamine	Germ cell mutagenicity: Positive and negative results were seen in various in Vitro and in Vivo studies
(DETDA)	Reproductive toxicity: Oral (Rat, females), Dose: 0, 50, 150, 500 mg/kg
CAS # 68479-98-1	General Toxicity Maternal: No observed adverse effect level: 50 mg/kg body weight
	Teratogenicity: No observed adverse effect level: 500 mg/kg body weight
	Embryo-fetal toxicity: No observed adverse effect level: 150 mg/kg body weight
	Embryotoxic effects and adverse effects on the offspring were detected only at high maternally toxic
	doses (OECD Test Guideline 414)
	STOT-RE: Oral (Rat), 90 days, Dose: 50-125-320ppm, NOEL: ≥8 mg/kg; LOEL: ≥21 mg/kg;
	Dermal (Rabbit), 21 day, Dose: 1-10-100mg/kg , NOEL: ≥10 mg/kg
	Chronic ingestion may cause liver damage. Pancreas damage.

Part No.: 60265W Date: August 25, 2021

Acute Toxicity

Oral LD50 (Rat): >5,110 mg/kg (OECD Guideline 401); May cause gastrointestinal tract irritation.

Dermal LD50 (Rabbit): Not data available

Inhalation LC50 (Rat)(dust/aerosol), 4hrs: >5.3 mg/L. Slightly irritant.

Skin corrosion/irritation (Rabbit): Slightly irritant. May cause dehydration.

Serious eye damage/eye irritation (Rabbit): Slightly irritant. May cause abrasion or mechanical

irritation.

Aspiration hazard: No

Chronic Toxicity

Sensitization: Skin - Not sensitizer (Guinea pig maximization test).

Respiratory - Negative effects of the Zeolites are minimized since they are dispersed in a liquid as opposed to an inhalable fine powder form. However, precautions should be taken to avoid breathing mists created by heating, mixing or spraying.

Germ cell mutagenicity: Risk to humans is not expected from exposure to this product.

Carcinogenicity: Not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP or EPA classification.

Reproductive toxicity: No adverse effects in rats and rabbits or their offspring following administration in the drinking water during pregnancy.

STOT-SE: Not classified.

STOT-RE: Not classified. Effects on kidney were observed in rats and dogs administered high dose levels in their feed for one month. Effect on blood, chronic pneumonitis and acute bronchopneumonia were observed in dogs. Long-term inhalation by rats and dogs produced inflammation in the lungs associated with accumulation of particulate.

Acute Toxicity

Oral LD50 (Rat): >5,000 mg/kg

Dermal LD50 (Rabbit): >5,000 mg/kg

Titanium dioxide does not penetrate either intact or abraded human skin.

Inhalation LC50 (Rat): >6.82 mg/l, 4 h

May cause irritation of respiratory tract. Inhalation of dust in high concentration may cause irritation of respiratory system.

Skin corrosion/irritation: No irritating effect. Powderized material may dry and mechanically irritate

Serious eye damage/eye irritation: No irritating effect. Like any foreign body, particles (dust) can cause mechanical irritation.

Chronic Toxicity

Sensitization: No sensitizing effects.

Germ cell mutagenicity: No classification is proposed, based on conclusive negative data.

Reproductive: Not classified.

(Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. However, other laboratory animals such as mice and hamsters did not develop lung tumors under similar testing with titanium dioxide. Furthermore, human epidemiology studies do not suggest an association

Carcinogenicity: IARC - Group 2B. Titanium dioxide is listed by IARC as possibly carcinogenic to humans

between occupational exposure to titanium dioxide and risk for cancer. Negative effects are minimized since it is dispersed in a liquid as opposed to an inhalable fine powder form. However, precautions should be taken to avoid breathing mists created by heating, mixing or spraying and dust

from cutting or grinding of cured product containing this component. STOT-SE: No classification is proposed, based on conclusive negative data.

STOT-RE: No classification is proposed, based on conclusive negative data.

CAS # 1318-02-1

Zeolites

Titanium Dioxide CAS # 13463-67-7

Date: August 25, 2021

	Acute Toxicity
	Oral LD50 (Rat): >2,000 mg/kg (Directive 67/548/EEC, Annex V.B.1)
	Dermal LD50 (Rat): >2,000 mg/kg (Directive 67/548/EEC, Annex V.B.3)
	Inhalation LC50 (Rat), 4hr: >4 mg/L dust/mist (OECD Guideline 403);
	Skin corrosion/irritation (Rabbit): slightly irritating (OECD Test Guideline 404)
	Serious eye damage/eye irritation (Rabbit): slightly irritating (OECD Test Guideline 405)
Confidential Component 1	<u>Chronic Toxicity</u>
CAS # Trade secret	Sensitization (Guinea pig): Skin-sensitizer (OECD Test Guideline 406)
	Germ cell mutagenicity: negative in vitro and in vivo tests
	Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is
	identified as probable, possible or confirmed human carcinogen by IARC, NTP, OSHA and ACGIH.
	Reproductive toxicity: Teratogenicity (Rat, Oral): NOAEL: 1,000 mg/kg
	STOT-SE: No data available.
	STOT-RE (Rat, Oral): NOAEL: >1,000 mg/kg
	Acute Toxicity
	Oral LD50 (Rat): 1,000-2,000 mg/kg; Harmful if swallowed. May cause gastrointestinal effects including
	nausea, lethargy and diarrhea.
	Dermal LD50 (Rabbit): >2,000 mg/kg
	Inhalation LC50 (Rat), 1hr: No data available.
	Skin corrosion/irritation (Rabbit): may cause slight irritation, but not expected to cause serious
	damage.
	Serious eye damage/eye irritation (Rabbit): may cause irritation (redness), but not expected to cause
Confidential Component 2	serious damage.
CAS # Trade secret	Aspiration hazard: No
	Chronic Toxicity
	Sensitization, skin and respiratory: Not sensitizer
	Germ cell mutagenicity: Risk to humans is not expected from exposure to this product.
	Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is
	identified as probable, possible or confirmed human carcinogen by IARC, NTP, OSHA and ACGIH.
	Reproductive: Risk to humans is not expected from exposure to this product.
	STOT-SE: Risk to humans is not expected from exposure to this product.
	STOT-RE: No known or reported target organs from repeated exposure.
The products in question	have been evaluated gaginst the Hazardous Products Regulations (WHMIS 2015) and no additional

The products in question have been evaluated against the Hazardous Products Regulations (WHMIS 2015) and no additional classifications, ingredient disclosure or exposure limits are required for those regulations.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:

Acutely and chronically hazardous for aquatic organisms. Do not release into natural waters.

Persistence and degradability:

Not readily biodegradable by OECD criteria. In contact with water the substance will hydrolyze slowly.

Bioaccumulative potential:

No significant accumulation in organisms is expected.

Mobility in soil:

Not known.

Other adverse effects:

Not known.

Toxicity test results:

This product itself has not been tested. Information given is based on data on the components and the toxicology of similar products.

Components	Test Results
Polyether Polyols Blend	Acute Toxicity
CAS # Trade secret	Fish LC50: >100 mg/, 96 h (based on available data and comparison to similar compounds)

Part No.: 60265W

Date: August 25, 2021

	Date: August 25, 2021
Diethyltoluenediamine (DETDA) CAS # 68479-98-1	Acute Toxicity Fish LC50 (Fathead minnow): >106 mg/l, 96 h (OECD Guideline 203) Aquatic Invertebrates EC50 (Daphnia magna): 5.8 mg/l, 48 h (OECD Guideline 202) Algae ErC50 (Green algae): 104 mg/l, 72 h (OECD Guideline 201) Ecological Data Microorganisms EC50 (bacterium): >170 mg/l, 24 h (DIN 38412 Part 8) Biodegradation, 28days: <1 % (OECD Guideline 301D); COD: 2,370 mg/g Summary: Very toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment.
Zeolites CAS # 1318-02-1	Acute Toxicity Fish LC50 (fathead minnow): >680 mg/l, 96 h (EPA 72-1, static). The details of the toxic effect relate to the nominal concentration. The LC50 is higher than the solubility limit. Aquatic invertebrates EC50 (Daphnia magna): 2,808 mg/l, 24 h (OECD Test Guideline 202, part 1, static) Aquatic plants EC50 (Green algae): >328 mg/l, 96 h (OECD Test Guideline 201, static). The details of the toxic effect relate to the nominal concentration. Tested above maximum solubility. The product has low solubility in the test medium. An eluate has been tested. Microorganisms EC50 (Bacteria): 950 mg/l, 16 h (Growth inhibition) (DIN 38412, Part 8). The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An eluate has been tested. Chronic Toxicity Fish (fathead minnow), 30days: NOEC: ≥86.7 mg/L (OPP 72-5, EPA-Guideline, Flow through). The statement of the toxic effect relates to the analytically determined concentration. Aquatic invertebrates (Daphnia magna), 21days: NOEC: 32 mg/L (OECD Test Guideline 211, semistatic). The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An eluate has been tested. Ecological Data Biodegradability: Not readily biodegradable. The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants. It cannot be eliminated from water by biological purification processes. Mobility in soil: Transport between environmental compartments: Study scientifically not justified.
Titanium Dioxide CAS # 13463-67-7	Aquatic Toxicity Fish LC50 (Orfe): >1,000 mg/l, 48 h Aquatic Invertebrates EC50 (Daphnia magna): 3 mg/l Algae/Aquatic Plants ErC50 (Pseudokirchneriella subcapitata): >100 mg/l, 72 h Ecological Data Persistence and degradability: Not readily biodegradable. Bioaccumulative potential: Titanium dioxide is persistent and does not bioaccumulate. Mobility in soil: Not mobile. Titanium dioxide is a stable compound that is insoluble in water and therefore would not be expected to be present in drinking water. Based on the lack of absorption as well as no identified toxicological effects of concern in animal testing, there are also no risk concerns for non-target terrestrial organisms resulting from the use of titanium dioxide as an inert ingredient.
Confidential Component 1 CAS # Trade secret	Acute Toxicity Fish LC50 (zebra fish): 10-100 mg/l, 96 h Aquatic invertebrates EC50 (Daphnia magna): 10-100 mg/l, 48 h Aquatic plants EC50 (green algae): >100 mg/l, 72 h Terrestrial plants (Oats), NOEC: ≥100 mg/kg Microorganisms EC50 (activated sludge): >3,000 mg/l, 3 h Ecological Data Biodegradation: DOC reduction, 28days: 0% not readily biodegradable Bioaccumulation: calculated value 1.872 BCF; hydrolyze rapidly in water

Date: August 25, 2021

Acute Toxicity

Fish LC50 (zebra fish): >100 mg/l, 96 h

Aquatic Invertebrates EC50 (Daphnia magna): >100 mg/l, 48 h

Aquatic Plants EC50 (algae): >100 mg/l, 72 h (Guideline 92/69/EEC, C.3)

Microorganisms EC20 (activated sludge): >1,000 mg/l, 0.5 h

Ecological Data

Confidential Component 2
CAS # Trade secret

Biodegradation: Not readily biodegradable.

Bioaccumulative potential: Does not significantly accumulate in organisms.

Mobility in soil: Not expected.

Product does not contain organically bound halogen.

Summary: High probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Product not tested; The statement has been

derived from substances/products of a similar structure or composition.

SECTION 13 – DISPOSAL CONSIDERATIONS

Product Disposal: The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

Container disposal: Even after emptying, container may retain residues. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation. This material and its container must be disposed of in a safe way.

SECTION 14 – TRANSPORT INFORMATION

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

BULK TRANSPORT

according to Annex II or MARPOL 73/78 and IBC Code

Not available

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

U.S. Toxic Substances Control Act:

None present or none present in regulated quantities.

US. EPA CERCLA Hazardous Substances (40 CFR 302) Components:

None present or none present in regulated quantities.

SARA Section 311/312 Hazard Categories:

Refer to hazard classification information in Section 2.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components:

None present or none present in regulated quantities.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required Components:

None present or none present in regulated quantities.

Part No.: 60265W
Date: August 25, 2021

US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

Massachusetts, New Jersey, Pennsylvania or Rhode Island Right to Know Substance Lists:

Titanium dioxide – CAS # 13463-67-7

California Prop. 65 Components:



WARNING: This product can expose you to chemicals including Titanium dioxide (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

NFPA Hazard Rating:

HEALTH	FIRE	INSTABILITY	SPECIFIC
2	1	1	
0 = Normal 1 = Slight 2 = Hazardous	(Flash Points)	0 = Stable 1 = Unstable if Heated 2 =	ACID (Acid) ALK (Alkaline) COR (Corrosive)
3 = Extreme Danger 4 = Deadly	0 = Will not burn 1 = Above 200°F	Violent Chemical Change 3 = Shock and	OXY (Oxidizer) W (Use No Water)
	2 = Below 200°F 3 = Below 100°F	Heat May Detonate 4 = May Detonate	
	4 = Below 73°F		

HMIS Hazard Rating:

HEALTH	FLAMMABILITY REACTIVITY		PROTECTIVE EQUIPMENT
2	1	1	X
0 = Normal	X = Ask your Supervisor or Safety Specialist		
	for handling instructions		

Canada regulations/legislation:

Hazardous Products Regulations (HPR): This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the Hazardous Products Regulations (HPR).

Domestic Substance List (DSL)/Non-Domestic Substance List (NDSL): All ingredients are listed on the DSL/NDSL.

International Regulations/Inventories:

No additional data available.

Date: August 25, 2021

SECTION 16 – OTHER INFORMATION

LEGEND

GHS Globally Harmonized System
CAS Chemical Abstracts Services
EC European Community

EPA Environmental Protection Agency

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety and Health

PEL Permissible Exposure Limits
TLV Threshold Limit Value

REL Recommended Exposure Limit
TWA Time-Weighted Average
STEL Short-term exposure limit

IARC International Agency for Research on Cancer

NTP National Toxicology Program

COD / BOD Chemical Oxygen Demand / Biological Oxygen Demand STOT, SE Specific Target Organ Toxicity following Single Exposure STOT, RE Specific Target Organ Toxicity following Repeated Exposure

DOT Department of Transportation

IMDG International maritime dangerous goods code

IATA, ICAO International Air Transport Association, International Civil Aviation Organization

TSCA Toxic Substances Control Act

EPCRA Emergency Planning and Community Right-to-Know Act

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CFR Code of Federal Regulations

RQ Reportable Quantity

EHS Extremely Hazardous Substances

DSL Domestic Substance List

WHMIS Workplace Hazardous Materials Information System

Latest revision date: August 25, 2021 - Internal Review

Date of the previous revision: N/A

Disclaimer: The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. **Rhino Linings Corporation** makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.