

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 1 of 14

Revision date: 02.11.2025**RhinoCoat FM (Flexible Membrane) Epoxy Resin****SECTION 1: Identification****Product Identifier****Product Name:** RhinoCoat FM (Flexible Membrane) Epoxy Resin**Product code:** RF200-FM-A**Recommended Use of the Product and Restriction on Use****Relevant Identified Uses:** EPOXY SYSTEM - Resin Component**Uses Advised Against:** Not determined or not applicable.**Reasons Why Uses Advised Against:** Not determined or not applicable.**Manufacturer or Supplier Details****Manufacturer:****United States**


Rhino Linings Corporation
9747 Businesspark Avenue
San Diego, CA 92131
858-450-0441
www.rhinolinings.com

Emergency Telephone Number:**North America**

CHEMTREC
800-424-9300 (24/7)

SECTION 2: Hazard(s) Identification**GHS Classification:**

Skin irritation, category 2
Eye irritation, category 2A
Skin sensitization, category 1
Chronic aquatic hazard, category 2

Label elements**Hazard Pictograms:****Signal Word:** Warning**Hazard statements:**

H315 Causes skin irritation
H319 Causes serious eye irritation
H317 May cause an allergic skin reaction
H411 Toxic to aquatic life with long lasting effects

Precautionary Statements:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 2 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P264 Wash any exposed skin thoroughly after handling.

P261 Avoid breathing dust, fumes, gas, mist, vapors or spray.

P272 Contaminated work clothing must not be allowed out of the workplace

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P273 Avoid release to the environment

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P362 Take off contaminated clothing and wash it before reuse

P321 Specific treatment (see Sections 4-8 of this SDS and any supplemental information on the product label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P405 Store locked up

P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	80-90
CAS Number: 68413-24-1	Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	10-20
CAS Number: 26142-30-3	Poly[oxy(methyl-1,2-ethanediyl)], α -(2-oxiranylmethyl)- ω -(2-oxiranylmethoxy)-	1-5
CAS Number: 64742-47-8	Distillates (petroleum), hydrotreated light	0.1-2

Additional Information:

Specific chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold.

Liquid Epoxy Resins (LERs) are made by reacting Bisphenol A or Bisphenol F with epichlorohydrin. Rhino Linings uses various CAS numbers for its LERs (25068-38-6, 25085-99-8, 1675-54-3 and 9003-36-5).

Accordingly, LER manufacturers consider that derivatives of LERs may be described using any of the CAS numbers referenced as a starting material.

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 3 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

Not determined or not applicable.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 4 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10). Recommended storage temperature: 10-35°C (50-95°F).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 350 mg/m ³ (up to 10 hr [petroleum distillates, naphtha])
	Distillates (petroleum), hydrotreated light	64742-47-8	Ceiling Limit: 1800 mg/m ³ ([15 min] petroleum distillates, naphtha)
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 100 mg/m ³ (up to 10 hr [kerosene])
OSHA	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 2000 mg/m ³ (500 ppm [aliphatic hydrocarbons])
United States(California)	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 1600 mg/m ³ (400 ppm [aliphatic hydrocarbons])

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 5 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA: 200 mg/m ³ (Kerosene and jet-fuels [non-aerosol], as total hydrocarbon vapor)

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Viscous liquid
Odor	Mild
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	200°C (392°F)
Flash point (closed cup)	200°C (392°F)
Evaporation rate	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 6 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

Strong oxidizing agents, acids, alkalis, amines, mercaptans.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Decomposition depends upon temperature, air supply and the presence of other materials. Gases are released during decomposition. Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	oral	LD50 Rat: 11400 mg/kg
	dermal	LD50 Rabbit: > 22800 mg/kg

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 7 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Name	Route	Result
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3- epoxypropane	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Distillates (petroleum), hydrotreated light	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5.28 mg/L (4 hr [vapor])

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane	Causes skin irritation.
Poly[oxy(methyl-1,2- ethanediyl)], α -(2- oxiranylmethyl)- ω -(2- oxiranylmethoxy)-	Causes skin irritation.
Distillates (petroleum), hydrotreated light	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane	Causes serious eye irritation.
Poly[oxy(methyl-1,2- ethanediyl)], α -(2- oxiranylmethyl)- ω -(2- oxiranylmethoxy)-	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 8 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Name	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	May cause an allergic skin reaction.
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	May cause an allergic skin reaction.
Poly[oxy(methyl-1,2-ethanediyl)], α -(2-oxiranylmethyl)- ω -(2-oxiranylmethoxy)-	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Not Applicable
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Not Applicable
Poly[oxy(methyl-1,2-ethanediyl)], α -(2-oxiranylmethyl)- ω -(2-oxiranylmethoxy)-	Not Applicable
Distillates (petroleum), hydrotreated light	Not Applicable

National Toxicology Program (NTP):

Name	Classification
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Not Applicable
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Not Applicable
Poly[oxy(methyl-1,2-ethanediyl)], α -(2-oxiranylmethyl)- ω -(2-oxiranylmethoxy)-	Not Applicable

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 9 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 10 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Product Data: No data available.

Substance Data:

Name	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Aquatic Invertebrates EC50 Daphnia magna: 2 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Scenedesmus capricornutum: 9.4 mg/L (72 hr [biomass])
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Aquatic Plants EC50 Desmodesmus subspicatus: >100 mg/L (72 hr [growth rate])
	Fish LC50 Danio rerio: >100 mg/L (96 hr [LL50])
	Aquatic Invertebrates EC50 Daphnia magna: >100 mg/L (48 hr [mobility])
Distillates (petroleum), hydrotreated light	Fish LC50 Oncorhynchus mykiss: 2 - 5 mg/L (96 hr [LL50; mortality])
	Aquatic Invertebrates EC50 Daphnia magna: 1.4 mg/L (48 hr [EL50; mobility])
	Aquatic Plants EC50 Raphidocelis subcapitata: 1 - 3 mg/L (72 hr [EL50; cell number])

Chronic (Long-Term) Toxicity

Assessment:

Toxic to aquatic life with long lasting effects.

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Fish NOEC Oncorhynchus mykiss: 0.098 mg/L (28 d [NOEL; mortality])
	Aquatic Invertebrates NOEC Daphnia magna: 0.89 mg/L (21 d [EL50; reproduction])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	The substance is not readily biodegradable. 5% degradation measured by O2 consumption after 28 days.
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	The substance is not readily biodegradable. 25.6% degradation in water, measured by CO2 evolution, after 29 days.
Distillates (petroleum), hydrotreated light	The substance is not readily biodegradable. 58.6% degradation in water, after 28 days.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 11 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Name	Result
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	The substance is not expected to bioaccumulate (BCF: 31 dimensionless) [QSAR].
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Standard bioaccumulation studies are not applicable to UVCB substances.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Standard adsorption/desorption studies are not applicable to UVCB substances.

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Distillates (petroleum), hydrotreated light	The substance is a UVCB and does not contain constituents included in the SVHC candidate list as PBT at concentrations above 0.1%.
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Standard PBT studies are not applicable to UVCB substances.

vPvB assessment:

Distillates (petroleum), hydrotreated light	The substance is a UVCB and does not contain constituents included in the SVHC candidate list as vPvB at concentrations above 0.1%.
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	Standard vPvB studies are not applicable to UVCB substances.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements.

Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

Contaminated packages:

Even after emptying, container may retain residues. Containers should be completely emptied and safely

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 12 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin


stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation. This material and its container must be disposed of in a safe way.

SECTION 14: Transport Information


United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None
Additional Information	This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

International Maritime Dangerous Goods (IMDG)

UN Number	UN3082
UN Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
UN Transport Hazard Class(es)	9 
Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
Additional Information	This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	UN3082
UN Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
UN Transport Hazard Class(es)	9 

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 13 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
Additional Information	This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	100 lbs for RCRA D001
------------	---	--------	-----------------------

RCRA:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	D001
------------	---	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
------------	---	--------

New Jersey Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
------------	---	--------

New York Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
------------	---	--------

Pennsylvania Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
------------	---	--------

California Proposition 65: None of the ingredients are listed.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Rhino Linings Corporation makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof. Sections 11/12 Disclaimer (Toxicity/Ecotoxicity): This product itself has not been

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.05.2019

Page 14 of 14

Revision date: 02.11.2025

RhinoCoat FM (Flexible Membrane) Epoxy Resin

tested. Information given is based on data on the components and the toxicology of similar products.
Section 14 (Transport Information): Information provided in Section 14 is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

NFPA: 2-1-0

HMIS: 2-1-0

Initial Preparation Date: 04.05.2019

Revision date: 02.11.2025

Revision Notes:

Revision Date	Notes
2019-04-05	New Product
2025-02-11	Internal Review / New SDS Software Program

End of Safety Data Sheet