



Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 1 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

SECTION 1: Identification

Product Identifier

Product Name: RhinoDecor Stamped Concrete Sealer

Product code: RF800-SCS

Recommended Use of the Chemical and Restrictions on Use:

Recommended Uses: FLOOR COATINGS: Concrete Restoration

Restrictions on Use: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Rhino Linings Corporation
1001 Ed Rutherford Road
Greenville, TX 75402
800-422-2603
www.rhinolinings.com

Emergency Telephone Number:

North America

CHEMTREC
800-424-9300 (24/7)

SECTION 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of § 1910.1200:

Flammable liquids, category 2
Skin irritation, category 2
Eye irritation, category 2A
Skin sensitization, category 1B
Reproductive toxicity, category 1B
Specific target organ toxicity - single exposure, category 3, narcotic effects

Label elements

Hazard Symbol(s):



Signal Word: Danger

Hazard statement(s):

H225 Highly flammable liquid and vapor
H315 Causes skin irritation
H319 Causes serious eye irritation
H317 May cause an allergic skin reaction
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness

Precautionary Statement(s):

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 2 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, and lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharge.

P261 Avoid breathing dust, fumes, gas, mist, vapours or spray.

P264 Wash any exposed skin thoroughly after handling.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P303+P361+P353 IN CASE OF SKIN CONTACT (or with hair): Immediately remove all contaminated clothing. Rinse skin with water.

P321 Specific treatment (see Sections 4-8 of this SDS and any supplemental information on the product label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use alcohol-resistant foam for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P404 Store in a closed container.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 67-64-1	Acetone	<65
CAS Number: 23262-63-7	Methyl/Butyl Methacrylate Copolymer	<20
CAS Number: 71808-49-6	Ketones, C11	<2
CAS Number: 98-56-6	4-Chloro- α,α,α -trifluorotoluene	<10
CAS Number: 85-68-7	Butyl benzyl phthalate	<4

Additional information:

Specific chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold.

SECTION 4: First Aid Measures

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 3 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Description of Necessary Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

After Ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury
Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing
Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness
Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time)
Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Immediate Medical Attention:

Skin/eye burns require immediate treatment
Overexposure via inhalation requires urgent medical treatment

Special Treatment:

No additional information.

Notes for the Doctor:

Treat symptomatically

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Dry chemical, CO₂, water spray or alcohol-resistant foam

Unsuitable Extinguishing Media:

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 4 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Do not use water jet

Specific Hazards Arising From The Chemical:

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation

Special Protective Equipment and Precautions for Fire-Fighters

Special Protective Equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode

Special precautions

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13)

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 5 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Acetone	67-64-1	8-Hour TWA: 250 ppm
	Acetone	67-64-1	15-Minute STEL: 500 ppm
	4-Chloro- α,α,α -trifluorotoluene	98-56-6	8-Hour TWA: 2.5 mg/m ³ (as Fluorides)
NIOSH	Acetone	67-64-1	REL-TWA: 590 mg/m ³ (250 ppm [up to 10-hr])
	Acetone	67-64-1	IDLH: 2500 ppm
	4-Chloro- α,α,α -trifluorotoluene	98-56-6	IDLH: 250 mg/m ³ (as Fluorides)
OSHA	Acetone	67-64-1	8-Hour TWA-PEL: 2400 mg/m ³ (1000 ppm)
	4-Chloro- α,α,α -trifluorotoluene	98-56-6	8-Hour TWA: 2.5 mg/m ³ (as Fluorides)
United States(California)	Acetone	67-64-1	8-Hour TWA-PEL: 1200 mg/m ³ (500 ppm)
	Acetone	67-64-1	Ceiling Limit: 3000 ppm
	Acetone	67-64-1	15-Minute STEL: 1780 mg/m ³ (750 ppm)
	4-Chloro- α,α,α -trifluorotoluene	98-56-6	PEL: 2.5 mg/m ³ (as Fluorides)

Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	Acetone	67-64-1	Acetone	Urine	End of shift	25 mg/L
	4-Chloro- α,α,α -trifluorotoluene	98-56-6	4-Chloro- α,α,α -trifluorotoluene	Urine	end of shift Fluoride background	3 mg/L
	4-Chloro- α,α,α -trifluorotoluene	98-56-6	4-Chloro- α,α,α -trifluorotoluene	Urine	prior to shift Fluoride background	2 mg/L

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Individual Protection Measures, Such as Personal Protective Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 6 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Physical state	Liquid
Color	Colorless / Cloudy
Odor (includes odor threshold)	Sweet Odor
Melting point/freezing point	Not Applicable
Initial boiling point/range	57 °C (135 °F)
Flammability	3-13%
Upper flammability/explosive limit	3% by volume/13%
Lower flammability/explosive limit	3% by volume/13%
Flash point	-18°C (0.4°F)
Auto-ignition temperature	465°C (869°F)
Decomposition temperature	300°C (572°F)
pH	Not Applicable
Kinematic viscosity	Not determined or not available.
Solubilities	Insoluble in Water
Partition coefficient (n-octanol/water)	Not determined or not available.
Vapor pressure (includes evaporation rate)	Not determined or not available.
Density and/or relative density	7.4 Lbs./Gal
Relative vapor density	3.7-4.0 (Air = 1)
Particle characteristics	Not determined or not available.

Other Information

VOC	<100 g/L or 0.83 #/Gallon
Volatiles	80-82%

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 7 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions, including those associated with foreseeable emergencies:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

Strong oxidizing agents.

Hazardous Decomposition Products:

Oxides of Carbon.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Acetone	oral	LD50 Rat: 5800 mg/kg
	inhalation	LC50 Rat: 76 mg/L (4 hr [Vapor])
	dermal	LD50 Rabbit: > 7426 mg/kg
4-Chloro- α,α,α -trifluorotoluene	oral	LD50 Rat: 5546 mg/kg
	inhalation	LC50 Rat: > 32.03 mg/L (4 hr [Aerosol])
	dermal	LD50 Rabbit: >3300 mg/kg
Butyl benzyl phthalate	oral	LD50 Rat: 2330 mg/kg
	dermal	LD50 Rabbit: >10,000 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
4-Chloro- α,α,α -trifluorotoluene	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Acetone	Causes serious eye irritation.
4-Chloro- α,α,α -trifluorotoluene	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 8 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

No data available.

Substance Data:

Name	Result
4-Chloro- α,α,α -trifluorotoluene	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Acetone	Not Applicable
Ketones, C11	Not Applicable
4-Chloro- α,α,α -trifluorotoluene	Group 2B
Butyl benzyl phthalate	Group 3

National Toxicology Program (NTP):

Name	Classification
Acetone	Not Applicable
Ketones, C11	Not Applicable
4-Chloro- α,α,α -trifluorotoluene	Not Applicable
Butyl benzyl phthalate	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment:

May damage fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
Butyl benzyl phthalate	May damage fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data:

Name	Result
Acetone	May cause drowsiness or dizziness.
Ketones, C11	May cause drowsiness or dizziness.
4-Chloro- α,α,α -trifluorotoluene	May cause respiratory irritation.

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 9 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Interactive effects:

No additional information.

Other Information:

No additional information.

SECTION 12: Ecological Information

Ecotoxicity

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Acetone	Fish LC50 Pimephales promelas: 8210 mg/L (96 hr)
	Aquatic Invertebrates LC50 Daphnia pulex: 8800 mg/L (48 hr)
4-Chloro- α,α,α -trifluorotoluene	Aquatic Plants EC50 Raphidocelis subcapitata: ≥ 0.41 mg/L (72 hr [growth rate])
	Aquatic Invertebrates LC50 Daphnia magna: 2 mg/L (48 hr [mobility])
	Fish LC50 Zebra Fish: 3 mg/L (96 hr)
Butyl benzyl phthalate	Fish LC50 Cymatogaster aggregata: 0.51 mg/L (96 hr)
	Aquatic Plants EC50 Scenedesmus subspicatus: 1.5 mg/L (72 hr [growth rate])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Acetone	Aquatic Invertebrates NOEC Daphnia magna: $>1106 - < 2212$ mg/L (28 d [mortality])
4-Chloro- α,α,α -trifluorotoluene	Aquatic Plants NOEC Raphidocelis subcapitata: 0.41 mg/L (72 hr [growth rate])
Butyl benzyl phthalate	Fish NOEC Pimephales promelas: 0.0646 - 0.0657 mg/L (126 d [survival, body length, body weight, number of spawns, percent fertility, percent hatchability])
	Aquatic Invertebrates EC50 Daphnia magna: >0.76 mg/L (21 d [mortality])

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 10 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Acetone	The substance is readily biodegradable. 90.9% degradation, measured by CO2 evolution, after 28 days.
4-Chloro- α,α,α -trifluorotoluene	The substance is not readily biodegradable. 19.2% degradation in water, measured by O2 consumption, after 28 days.
Butyl benzyl phthalate	The substance is readily biodegradable. 77.7% degradation in water, measured by CO2 evolution, after 28 days.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Acetone	Bioaccumulation is not expected. Calculated BCF (aquatic species): 3
4-Chloro- α,α,α -trifluorotoluene	The substance has a low potential for bioaccumulation (BCF (aquatic species): 121.8 dimensionless).
Butyl benzyl phthalate	The substance has the potential to bioaccumulate (BCF: 188 dimensionless, basis: whole body w.w., species: Lepomis macrochirus).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Acetone	The substance is mobile in soil with very low potential for adsorption to soil and sediment. Soil sorption Kd: 1.5 L/kg, at 20 °C
4-Chloro- α,α,α -trifluorotoluene	The substance is moderately mobile, therefore, there is moderate potential for adsorption to soil and sediment (Koc: 420 at 20 °C).
Butyl benzyl phthalate	The substance is slightly mobile, therefore, adsorption to soil and sediment is expected (log Koc: 3.41, QSAR substance data).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Acetone	The substance is not PBT.
4-Chloro- α,α,α -trifluorotoluene	The substance is not PBT.
Butyl benzyl phthalate	The substance is not PBT

vPvB assessment:

Acetone	The substance is not vPvB.
4-Chloro- α,α,α -trifluorotoluene	The substance is not vPvB.
Butyl benzyl phthalate	The substance is not vPvB

Other Adverse Effects: No additional information.

SECTION 13: Disposal Considerations

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 11 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

Disposal Methods:

The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

Contaminated packaging:

Even after emptying, container may retain residues. Containers should be completely emptied and safely stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation. This material and its container must be disposed of in a safe way.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN1263
UN Proper Shipping Name	PAINT
UN Transport Hazard Class(es)	3 
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	UN1263
UN Proper Shipping Name	PAINT
UN Transport Hazard Class(es)	3 
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	UN1263
UN Proper Shipping Name	PAINT
UN Transport Hazard Class(es)	3 
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	Not Applicable
Ship Type	Not Applicable
Pollution Category	Not Applicable

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 12 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA:

67-64-1	Acetone	Listed	5000 lb
85-68-7	Butyl benzyl phthalate	Listed	100 lbs

RCRA:

67-64-1	Acetone	Listed	U002
85-68-7	Butyl benzyl phthalate	Listed	F039

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

67-64-1	Acetone	Listed
85-68-7	Butyl benzyl phthalate	Listed

New Jersey Right to Know:

67-64-1	Acetone	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Listed
85-68-7	Butyl benzyl phthalate	Listed

New York Right to Know:

67-64-1	Acetone	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Listed
85-68-7	Butyl benzyl phthalate	Listed

Pennsylvania Right to Know:

67-64-1	Acetone	Listed
85-68-7	Butyl benzyl phthalate	Listed

California Proposition 65:

⚠ WARNING: This product can expose you to 4-Chloro- α,α,α -trifluorotoluene; which is known to the State of California to cause cancer; and Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: No additional information.

SECTION 16: Other Information

Disclaimer:

The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Rhino Linings Corporation makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof. SECTION 2 Disclaimer (Workplace Hazard Classification): Hazard classifications presented in Section 2 are developed in accordance with applicable hazard communication regulations and are intended to communicate workplace health, physical, and environmental hazards associated with handling and use of the product. Transportation classifications presented in Section 14 are assigned in accordance with applicable dangerous goods transport regulations and are based on separate classification criteria. Consequently, hazard classifications shown

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.21.2011

Page 13 of 13

Revision date: 07.31.2026

RhinoDecor Stamped Concrete Sealer

in Section 2 may not directly correspond to transportation classifications shown in Section 14. Sections 11/12 Disclaimer (Toxicity/Ecotoxicity): This product itself has not been tested. Information given is based on data on the components and the toxicology of similar products. SECTION 14 (Transport Information): Information provided in Section 14 is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Transportation classifications are assigned to the product as supplied and are based on the properties of the finished formulation. The transport classifications of individual raw materials or ingredients do not necessarily apply to the finished product.

NFPA: 2-3-0

HMIS: 2-3-0-X

Initial Preparation Date: 09.21.2011

Revision date: 07.31.2026

Revision Notes:

Revision Date	Notes
2011-09-21	
2016-02-16	Internal Review
2020-10-20	Product Name Change (formerly SCS)
2021-01-26	Internal Review Against Raw Material SDS - Composition Edits
2026-07-31	Internal Review

End of Safety Data Sheet